GUJARAT TECHNOLOGICAL UNIVERSITY BE - SEMESTER-III (New) EXAMINATION – WINTER 2015

Subject Name: Mechanics of Solids			ate:05/01/2016	
			arks: 70	
	2. M	ttempt all questions. Iake suitable assumptions wherever necessary. igures to the right indicate full marks.		
			Marks	
Q.1		Short Questions (each question carry one Mark)	14	
-	a	Define Pappu's Guldinus theorem- I		
	b	Define Principle of Superposition		
	c	Define law of Transmissibility		
	d	Define Couple		
	e f	Enlist types of supports. Sketch qualitative shear stress distribution diagrams of 'I' section of the beams.		
	g	Give mathematical expression of Lami's theorem,		
	_	Fill in the blanks		
	h	Lateral strains are longitudinal strains.		
	i	(sometimes less than, always less than, never less than) The shape of shear force diagram for cantilever beam subjected to couple at free end is [horizontal straight line, zero, parabola, incline straight line].		
	j	Moment is a vector, whereas Couple is a vector.		
		(free, null, fixed)		
	k	At the point of contraflexure changes its sign.		
	1	(shear force, bending moment, axial force) The Relation between Shear force and Bending moment is		
	m	The relation between, dynamic coefficient of friction (μ d) is static coefficient of friction (μ s). (less then/		
	n	greater then/Equal to) Relation between Modulus of Elasticity and Bulk Modulus is		
Q.2	(a)	Write assumption made in the theory of pure bending.	03	
	(b)	State and Prove with usual notation 'The law of Parallelogram'.	04	
	(c)	The forces are acting on a rigid body as shown in Figure 1 . Find the resultant of the given force system, in terms of magnitude and direction. Find the location of Resultant with respect to point A. OR	07	
	(c)	Determine centroid of the section shown in Figure 2 .	07	
Q.3	(e) (a)	At a point in a strained material, the state of stress is as shown in figure 3. Determine (i) principal stresses	03	
	(b)	For problem above in Q.3 (a), figure 3 calculate (i) location of principal planes and (ii) maximum shear stress and its location.	04	

(c) Draw shear force diagram and bending moment diagram for beam 07 shown in figure 4.

OR

- Q.3 (a) A solid steel shaft has to transmit 350 kW at 900 r.p.m. Find the diameter of the shaft if the shear stress is to be limited to 125 N/mm². Calculate the diameter of the shaft.
 - (b) A solid steel shaft has to transmit 350 kW at 900 r.p.m. Find the diameter of the shaft if the shear stress is to be limited to 125 N/mm². Calculate the diameter of the shaft if hollow shaft is provided of internal diameter equals 0.75 times external diameter
 - (c) A simply supported beam 10 m long carries three point loads at 50 kN, 60 kN and 80 kN at 3m, 5m and 8m from left support. Draw S.F. and B.M. diagram for the beam.
- **Q.4** (a) Define friction and State laws of Dry friction.
 - (b) The T-section is manufactured by connecting two equal rectangular 04 blocks having size 200 mm x 30 mm. Determine moment of inertia of the section about its horizontal axis.
 - (c) Find the magnitude of the Horizontal force 'P' applied to the lower 07 block to cause impending motion as shown in **figure 5.** Take $\mu = 0.3$ at all contact surfaces. Weight of block 'A' is 300 N and weight of block 'B' is 1200 N.

OR

- Q.4 (a) Determine reaction at supports for the Beam as shown in Figure 6. 03
 - (b) Determine deformation in each part of the bar ABCD shown in **04** Figure 7. Take $E = 2 \times 10^5 \text{ N/mm}^2$.
 - (c) A uniform ladder AB weighing 230 N and 4m long, is supported by vertical wall at top end B and by horizontal floor at bottom end A. A man weighing 550 N stood at the top of the ladder. Determine minimum angle θ of ladder AB with floor for the stability of ladder. Take co efficient of friction between ladder and wall as 1/3 and between ladder and floor as 1/4.
- Q.5 (a) Derive formula for determine volumetric strain of circular bar of diameter 'd', length 'L', modulus of elasticity 'E' subjected to axial tensile force 'P' and Poisson's ratio 'µ'.
 - (b) The Rectangular block of size 300mm (b) x 450mm (d) is subjected 04 to a uniform bending moment 120 kNm. Calculate the bending stresses at extreme fiber of the blocks. Also, find out total tensile and compressive forces due to bending stresses. Draw bending stress distribution diagram also.
 - (c) A rectangular block of size 350mm (l) x 50mm (b) x 150mm (h) is **07** subjected to forces shown in **figure 8**. $E = 2 \times 10^5 \text{ N/mm}^2$ and Poisson's ratio is 0.28, calculate the Change in volume of block.

OR

- **Q.5** (a) State the condition of equilibrium for Co-planner force system. 03
 - (b) The Rectangular block of size 300mm (b) x 450mm (d) is subjected 04 to a shear force 80 kN. Calculate the Shear stresses at neutral axis and Junction of the blocks. Draw Shear stress distribution diagram also.
 - (c) A system of connected flexible cables shown in figure 9 is supporting 07 two vertical forces 300 N and 400 N at points B and D. determine the forces in various segments of the cable.

03

